

TECHNICAL DATA SHEET

Readyline Survey Marker Spray Paint

750ml aerosol | Seven-colour range

Product overview

Readyline is a lead-free, resin-based marker paint supplied in a large 750ml aerosol. It produces highly visible, hard-wearing and weather-resistant marks on compatible surfaces including asphalt, concrete and steel. Suitable for surveying, construction, civil engineering, warehouses, car parks, roads and sports areas, indoors or outdoors.



Readyline branded can

COLOUR RANGE

Readyfix code	Colour
Z631-057	White
Z631-067	Red
Z631-077	Blue
Z631-087	Yellow
Z631-097	Green
Z631-098	Orange
Z631-099	Black

KEY PERFORMANCE

Dust dry	Approx. 15 minutes
Touch dry	Approx. 25 minutes
Overworkable	Approx. 24 hours
Typical colour life	Up to approx. 6 months*
Aerosol emission rate	≥96% (supplier stated)
Shelf life	24 months in suitable storage

Drying figures are stated at 20°C and 50% relative humidity. Actual drying, coverage and durability depend on temperature, humidity, substrate, layer thickness, traffic, weathering and UV exposure.

DIRECTIONS FOR USE

- Read and observe the can label and Safety Data Sheet before use.
- Ensure the surface is clean, dry and free from loose contamination.
- Shake the can vigorously for 2 minutes.
- Invert and spray downwards from 50-75mm. Moving closer produces a narrower, more accurate line; movement speed controls paint density.
- Use masking tape where sharper or more accurate lines are required.
- After use, hold the can upright, point away from the user and spray briefly to clear the nozzle.

TECHNICAL PROPERTIES

Paint type	Lead-free, resin based
Container	750ml aerosol; approx. 450g net
Propellant	LPG
Application	Indoor and outdoor
Primer	Normally not required
Application temperature	+5°C to +40°C
Typical coverage	Approx. 100m per can*
Film thickness	Approx. 130-150µm at 1.5 cross coats

STORAGE AND SAFETY

Store sealed in a dry, well-ventilated place away from sunlight, heat, sparks and flames; do not expose above 50°C. Follow the can label and current Safety Data Sheet for PPE, first aid, transport and disposal.

TECHNICAL NOTE

*Coverage and colour life are approximate and depend on application and service conditions. Test a small area first to confirm adhesion, appearance and compatibility. This sheet describes the Readyline-branded product manufactured to the current supplier technical specification.